

Test report No:
6070459.50

TEST REPORT

Electromagnetic Compatibility (EMC)

Identification of item tested	Concrete Grinder
Trademark	AGP
Model and /or type reference	G180
Ratings	220-240 V; 50-60 Hz; 1800 W; n: 3500-5800 /min; Ø180 mm; Class II 230-240 V; 50-60 Hz; 2000 W; n: 3500-5800 /min; Ø180 mm; Class II 110-120 V; 50-60 Hz; 1500 W; n: 3500-5800 /min; Ø180 mm; Class II
Test Laboratory / address	DEKRA Testing and Certification (Shanghai) Ltd.
Applicant / address	LEE YEONG INDUSTRIAL CO., LTD. No.2, Kejia Rd., Douliu City, Yunlin County 64057, Taiwan
Test method requested, standard	EN 55014-1:2017; EN 55014-2:2015; EN 61000-3-2:2014; EN 61000-3-3:2013
Verdict Summary	IN COMPLIANCE
Tested by	Kaiyuan Dai (Project Engineer) 
Approved by	Zuyao Fan (Project Manager) 
Date of issue	2020-06-23
Report template No	TRF_EN55014-1_EN55014-2_EMC02 V1.0

INDEX

	page
Competences and Guarantees.....	4
General conditions.....	4
Uncertainty	5
Environmental conditions	5
Possible test case verdicts.....	6
Definition of symbols used in this test report.....	6
Abbreviations.....	6
Document History	7
Remarks and Comments	7
1 General Information	8
1.1 General Description of the Item(s).....	8
1.2 Environment.....	10
1.3 Test Location	10
1.4 Classification according to EN 55014-2	11
2 Description of Test Setup	12
2.1 Operating mode(s) used for tests	12
2.2 Port(s) of the EUT	12
2.3 Support / Auxiliary equipment / unit / software for the EUT.....	12
2.4 Test Configuration / Block diagram used for tests	13
3 Verdict summary section	14
3.1 Standards	14
3.2 Deviation(s) from the Standard(s) / Test Specification(s).....	14
3.3 Overview of results.....	15
4 Emission Test Results.....	16
4.1 Conducted disturbance voltage – Mains	16
4.2 Conducted disturbance voltage– Load terminals.....	26
4.3 Conducted disturbance voltage– Additional terminals	27
4.4 Disturbance power (30 MHz – 300 MHz)	28
4.5 Radiated electromagnetic disturbances (30 – 1000 MHz)	32
4.6 Discontinuous disturbance (clicks) on AC power leads	33
4.7 Harmonic current emissions	34
4.8 Voltage changes, voltage fluctuations and flicker.....	38
5 Immunity Test Results.....	40
5.1 Performance (Compliance) criteria	40

5.1.1	Performance criteria related to immunity tests.....	40
5.1.2	Manufacturer defined performance criteria.....	40
5.2	Monitored – Checked Functions / Parameters	41
5.3	Electrostatic discharge immunity	42
5.4	Radio-frequency electromagnetic fields immunity	43
5.5	Electrical Fast Transients immunity	44
5.6	Surge transient immunity.....	45
5.7	Injected currents (RF common mode) immunity.....	46
5.8	Power supply interruptions and dips immunity	47
6	Identification of the Equipment Under Test	48
7	Measurement Uncertainties.....	49
8	Used Equipment	50
9	Test Photos.....	52

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.
5. The information provided by the customer in this report may affect the validity of the results, the test lab is not responsible for it.
6. The test results presented in this report relate only to the object tested.

UNCERTAINTY

For all measurements where guidance for the calculation of the instrumentation uncertainty of a measurement is specified in EN 55016-4-2 (CISPR 16-4-2), EN/IEC 61000-4 series or a product standard, the measurement instrumentation uncertainty has been calculated and applied in accordance with these standards.

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%
Atmospheric pressure	86 kPa – 106 kPa

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

DEFINITION OF SYMBOLS USED IN THIS TEST REPORT

<input checked="" type="checkbox"/> Indicates that the listed condition, standard or equipment is applicable for this report/test/EUT.			
<input type="checkbox"/> Indicates that the listed condition, standard or equipment is not applicable for this report/test/EUT.			
Decimal separator used in this report	<input checked="" type="checkbox"/>	Comma (,)	<input type="checkbox"/> Point (.)

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	:	Equipment Under Test
QP	:	Quasi-Peak
CAV	:	CISPR Average
AV	:	Average
CDN	:	Coupling Decoupling Network
SAC	:	Semi-Anechoic Chamber
OATS	:	Open Area Test Site
BW	:	Bandwidth
AM	:	Amplitude Modulation
PM	:	Pulse Modulation
HCP	:	Horizontal Coupling Plane
VCP	:	Vertical Coupling Plane
U_N	:	Nominal voltage

DOCUMENT HISTORY

Report nr.	Date	Description
6070459.50	2020-06-23	First release

REMARKS AND COMMENTS

The equipment under test (EUT) does meet the requirements of the stated standard(s)/test(s).

The test results relate only to the samples tested.

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Description of the item	Concrete Grinder
Model / Type number	G180
Trademark	AGP
Manufacturer.....	LEE YEONG INDUSTRIAL CO., LTD. No.2, Kejia Rd., Douliu City, Yunlin County 64057, Taiwan
Factory	LEE YEONG INDUSTRIAL CO., LTD. No.2, Kejia Rd., Douliu City, Yunlin County 64057, Taiwan


Rated Power	220-240 V; 50-60 Hz; 1800 W; n: 3500-5800 /min; Ø180 mm; Class II 230-240 V; 50-60 Hz; 2000 W; n: 3500-5800 /min; Ø180 mm; Class II 110-120 V; 50-60 Hz; 1500 W; n: 3500-5800 /min; Ø180 mm; Class II
Clock frequencies	Not provided
Other parameters.....	N/A
Mounting position.....	<input type="checkbox"/> Table top equipment
	<input type="checkbox"/> Wall/Ceiling mounted equipment
	<input type="checkbox"/> Floor standing equipment
	<input checked="" type="checkbox"/> Hand-held equipment
	<input type="checkbox"/> Other:

Intended use of the Equipment Under Test (EUT)	
N/A	

No	Module/parts of test item	Type	Manufacturer
	N/A		

No	Documents as provided by the applicant – Description	File name	Issue date
	N/A		

Copy of marking plate:



1.2 Environment

The requirements and standards apply to equipment intended for use in:

<input checked="" type="checkbox"/>	Residential (domestic) environment.
<input checked="" type="checkbox"/>	Commercial and light-industrial environment.
<input type="checkbox"/>	Industrial environment.

1.3 Test Location

Location	DEKRA Testing and Certification Co.,Ltd.
Address	No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C
Date	2020-04
Supervised by	Kaiyuan Dai

1.4 Classification according to EN 55014-2

The standard EN 55014-2 is subdivided in four categories. For each category, specific immunity requirements are formulated.

<input type="checkbox"/>	<p>Category I: Apparatus containing no electronic control circuitry.</p> <p><u>Examples:</u> Motor operated appliances, lighting toys, track sets without electronic control units, tools, heating appliances, UV and IR radiators and apparatus containing components such as electromechanical switches and thermostats.</p> <p>Electric circuits consisting of passive components (such as radio interference suppression capacitors or inductors, mains transformers and mains frequency rectifiers) are not considered to be electronic control circuitry.</p>
<input checked="" type="checkbox"/>	<p>Category II: Transformer toys, dual supply toys, mains powered motor operated appliances, tools, heating appliances and similar electric apparatus (for example – UV radiators, IR radiators and microwave ovens) containing electronic control circuitry with no internal clock frequency or oscillator frequency higher than 15 MHz.</p>
<input type="checkbox"/>	<p>Category III: Battery powered apparatus (with built-in batteries or external batteries), which in normal use is not connected to the mains, containing an electronic control circuitry with no internal clock frequency or oscillator frequency higher than 15 MHz.</p>
<input type="checkbox"/>	<p>Category IV: All other apparatus covered by the scope of the EN 55014-2 standard.</p>
<p>Clock frequency: Fundamental frequency of any signal used in the device, excluding those which are solely used inside integrated circuits (IC).</p>	

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

Operating mode	Operating mode description	Used for testing	
		Emission	Immunity
1	Normal operation	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
2		<input type="checkbox"/>	<input type="checkbox"/>
3		<input type="checkbox"/>	<input type="checkbox"/>
4		<input type="checkbox"/>	<input type="checkbox"/>
5		<input type="checkbox"/>	<input type="checkbox"/>
6		<input type="checkbox"/>	<input type="checkbox"/>
<u>Supplemental information:</u>			

2.2 Port(s) of the EUT


Port name and description	Connected to / Termination	Cable		
		Length used during test [m]	Attached during test	Shielded
N/A			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
<u>Supplemental information:</u>				

2.3 Support / Auxiliary equipment / unit / software for the EUT

The EUT has been tested with the following auxiliary equipment / unit / software:

Auxiliary equipment / unit / software	Type / Version	Manufacturer	Supplied by
N/A			
<u>Supplemental information:</u>			

2.4 Test Configuration / Block diagram used for tests



3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
EN 55014-1	2017 ¹⁾	Requirements for household appliances, electric tools and similar apparatus – Part 1: Emission.
EN 55016-2-1	2014	Methods of measurement of disturbances and immunity – Conducted disturbance measurements.
EN 55016-2-2	2010	Methods of measurement of disturbances and immunity – Measurement of disturbance power.
EN 55016-2-3 +A1 +A2	2010 2010 2014	Methods of measurement of disturbances and immunity – Radiated disturbance measurements.
EN 61000-3-2	2014	Limits for harmonic current emissions (equipment input current ≤ 16 A per phase).
EN 61000-3-3	2013	Limitation of voltage fluctuations and flicker
EN 55014-2	2015 ¹⁾	Requirements for household appliances, electric tools and similar apparatus – Part 2: Immunity – Product family standard.
EN 61000-4-2	2009	Electrostatic discharge immunity test.
EN 61000-4-3 +A1 +A2	2006 2008 2010	Radiated, radio-frequency, electromagnetic field immunity test.
EN 61000-4-4	2012	Electrical fast transient/burst immunity test.
EN 61000-4-5	2014	Surge immunity test.
EN 61000-4-6	2014	Immunity to conducted disturbances, induced by radio-frequency fields.
EN 61000-4-11	2004	Voltage dips, short interruptions and voltage variations immunity tests.

50) Not harmonized yet.

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

No deviation.

3.3 Overview of results

EMISSION TESTS – EN 55014-1			
Requirement – Test case	Basic standard(s)	Verdict	Remark
Conducted disturbance voltage at mains terminals (150 KHz – 30 MHz)	EN 55016-2-1	PASS	---
Conducted disturbance voltage at load terminals (150 KHz – 30 MHz)	EN 55016-2-1	N/A	---
Conducted disturbance voltage at additional terminals (150 KHz – 30 MHz)	EN 55016-2-1	N/A	---
Disturbance power (30 MHz to 300 MHz)	EN 55016-2-2	PASS	See 2)
Radiated electromagnetic disturbances (30 – 1000 MHz)	EN 55016-2-3	N/A	---
Discontinuous disturbance (clicks) on AC power leads	EN 55014-1	N/A	See 1)
<u>Supplementary information:</u>			
1) Exemptions from click measurements applicable (clause 4.2.3).			
2) According to clause 4.1.2.3.2 procedure (a) of the EN 55014-1 standard the EUT is deemed to comply in the frequency range from 300 MHz to 1000 MHz without further measurements.			

EMISSION TESTS – EN 61000-3-2, EN 61000-3-3			
Requirement – Test case	Basic standard(s)	Verdict	Remark
Harmonic current emissions	EN 61000-3-2	PASS	---
Voltage changes, voltage fluctuations and flicker	EN 61000-3-3	PASS	---
<u>Supplementary information:</u>			

IMMUNITY TESTS – EN 55014-2			
Requirement – Test case	Basic standard(s)	Verdict	Remark
Electrostatic discharge	EN 61000-4-2	PASS	---
Radio-frequency electromagnetic fields	EN 61000-4-3	N/A	---
Fast transients	EN 61000-4-4	PASS	---
Surge transient	EN 61000-4-5	PASS	---
Injected currents (radio-frequency common mode)	EN 61000-4-6	PASS	---
Voltage dips and short interruptions	EN 61000-4-11	PASS	---
<u>Supplementary information:</u>			

4 EMISSION TEST RESULTS

4.1	Conducted disturbance voltage – Mains	VERDICT: PASS
------------	--	----------------------

Standard	EN 55014-1
Basic standard	EN 55016-2-1

Limits – Tools

Frequency range [MHz]	Limit: QP [dB(μV) ^{1]}	Limit: AV [dB(μV) ^{1]}	IF BW	Detector(s)
0,15 - 0,35	66 – 56 ²⁾	59 - 46 ²⁾	9 KHz	QP, CAV
0,35 - 5,0	56	46	9 KHz	QP, CAV
5,0 - 30	60	50	9 KHz	QP, CAV

¹⁾ At the transition frequency, the lower limit applies.

²⁾ The limit decreases linearly with the logarithm of the frequency.


<input type="checkbox"/>	Rated power below 700 W	Limits as above
<input type="checkbox"/>	Rated power between 700 and 1000 W	Limits +4 dB
<input checked="" type="checkbox"/>	Rated power above 1000 W	Limits +10 dB

Performed measurements

Scan range (0,9 – 1,1 U _N)	<input type="checkbox"/> 198 – 264 V _{AC}	<input type="checkbox"/> 207 – 253 V _{AC}	<input checked="" type="checkbox"/> 230 V _{AC}
Tested terminal(s) / port	<input checked="" type="checkbox"/> AC mains input power	<input checked="" type="checkbox"/> N	<input checked="" type="checkbox"/> L1
	<input type="checkbox"/> DC mains input power	<input type="checkbox"/> Positive (+)	<input type="checkbox"/> Negative (-)
Voltage – Mains [V]	230 Vac		
Frequency – Mains [Hz]	50 Hz		
Test method applied	<input checked="" type="checkbox"/> Artificial mains network		
	<input type="checkbox"/> Voltage probe		
Test setup	<input type="checkbox"/> Table top	<input checked="" type="checkbox"/> Artificial hand applied	
	<input type="checkbox"/> Floor standing	<input type="checkbox"/> Other:	
Refer to the Annex 3 for test setup photo(s).			
Operating mode(s) used	Mode 1		
Remark	---		

Measurement data	Port under test	AC mains power input
Operating mode / voltage / frequency used during the test		Mode 1/ 230 Vac/ 50 Hz

Line




No	Frequency (MHz)	Emission Level (dBuV)	Limit (dBuV)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	0.155	62.36	75.82	-13.46	52.69	9.67	QP
2	0.155	51.09	68.75	-17.66	41.42	9.67	AV
3	0.244	64.54	72.72	-8.18	54.85	9.69	QP
4	0.244	44.69	64.31	-19.62	35.00	9.69	AV
5	0.287	65.21	71.19	-5.99	55.51	9.70	QP
6	0.287	43.08	62.13	-19.05	33.39	9.70	AV
7	0.33	65.92	69.71	-3.79	56.21	9.71	QP
8	0.33	43.69	60.02	-16.33	33.98	9.71	AV
*9	0.381	66.19	69.00	-2.81	56.47	9.72	QP
10	0.381	43.81	59.00	-15.19	34.09	9.72	AV
11	0.406	65.95	69.00	-3.05	56.23	9.72	QP
12	0.406	43.22	59.00	-15.78	33.50	9.72	AV
13	0.427	66.06	69.00	-2.94	56.33	9.73	QP
14	0.427	44.16	59.00	-14.84	34.44	9.73	AV
15	0.494	64.52	69.00	-4.48	54.77	9.74	QP
16	0.494	43.97	59.00	-15.03	34.23	9.74	AV
17	0.547	62.82	69.00	-6.18	53.07	9.75	QP

Measurement data			Port under test		AC mains power input		
18	0.547	45.59	59.00	-13.41	35.84	9.75	AV
19	1.056	53.31	69.00	-15.69	43.49	9.82	QP
20	1.056	40.35	59.00	-18.65	30.53	9.82	AV
21	2.028	51.17	69.00	-17.83	41.32	9.85	QP
22	2.028	33.97	59.00	-25.03	24.12	9.85	AV
23	3.617	46.80	69.00	-22.20	36.91	9.90	QP
24	3.617	28.26	59.00	-30.74	18.36	9.90	AV
25	6.153	41.31	74.00	-32.69	31.34	9.97	QP
26	6.153	28.96	64.00	-35.04	18.99	9.97	AV
27	10.172	37.09	74.00	-36.91	26.97	10.11	QP
28	10.172	23.81	64.00	-40.19	13.70	10.11	AV
29	18.728	50.74	74.00	-23.26	40.48	10.26	QP
30	18.728	33.79	64.00	-30.21	23.53	10.26	AV
31	21.784	19.24	74.00	-54.76	8.95	10.29	QP
32	21.784	9.79	64.00	-54.21	-0.50	10.29	AV
33	28.428	12.77	74.00	-61.23	2.44	10.33	QP
34	28.428	6.92	64.00	-57.08	-3.41	10.33	AV
Remark							

Measurement data	Port under test	AC mains power input
Operating mode / voltage / frequency used during the test		Mode 1/ 230 Vac/ 50 Hz

Neutral



No	Frequency (MHz)	Emission Level (dBuV)	Limit (dBuV)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	0.163	65.81	75.56	-9.74	56.14	9.67	QP
2	0.163	50.72	68.37	-17.65	41.05	9.67	AV
3	0.257	66.32	72.27	-5.94	56.63	9.69	QP
4	0.257	46.16	63.67	-17.50	36.47	9.69	AV
5	0.309	67.00	70.42	-3.42	57.30	9.70	QP
6	0.309	45.10	61.03	-15.93	35.40	9.70	AV
7	0.348	67.05	69.06	-2.01	57.34	9.71	QP
8	0.348	45.11	59.09	-13.98	35.40	9.71	AV
*9	0.381	67.26	69.00	-1.74	57.55	9.72	QP
10	0.381	45.30	59.00	-13.70	35.59	9.72	AV
11	0.412	67.12	69.00	-1.88	57.40	9.72	QP
12	0.412	45.72	59.00	-13.28	36.00	9.72	AV
13	0.447	66.64	69.00	-2.36	56.91	9.73	QP
14	0.447	45.79	59.00	-13.21	36.06	9.73	AV
15	0.549	63.96	69.00	-5.04	54.21	9.75	QP
16	0.549	47.71	59.00	-11.29	37.96	9.75	AV
17	1	54.29	69.00	-14.71	44.47	9.82	QP


Measurement data				Port under test		AC mains power input	
18	1	41.97	59.00	-17.03	32.15	9.82	AV
19	1.946	51.11	69.00	-17.89	41.26	9.85	QP
20	1.946	34.92	59.00	-24.08	25.07	9.85	AV
21	3.563	47.30	69.00	-21.70	37.41	9.90	QP
22	3.563	27.36	59.00	-31.64	17.47	9.90	AV
23	6.041	41.69	74.00	-32.31	31.71	9.98	QP
24	6.041	28.14	64.00	-35.86	18.16	9.98	AV
25	10.13	37.36	74.00	-36.64	27.22	10.14	QP
26	10.13	22.47	64.00	-41.53	12.33	10.14	AV
27	17.99	48.25	74.00	-25.75	37.88	10.37	QP
28	17.99	31.20	64.00	-32.80	20.82	10.37	AV
29	21.103	23.62	74.00	-50.38	13.17	10.45	QP
30	21.103	11.67	64.00	-52.33	1.22	10.45	AV
31	28.862	11.20	74.00	-62.80	0.63	10.57	QP
32	28.862	6.26	64.00	-57.74	-4.31	10.57	AV
Remark							

Performed measurements

Scan range (0,9 – 1,1 U_N)	<input type="checkbox"/>	198 – 264 V_{AC}	<input type="checkbox"/>	207 – 253 V_{AC}	<input checked="" type="checkbox"/>	120 V_{AC}				
Tested terminal(s) / port	<input checked="" type="checkbox"/>	AC mains input power	<input checked="" type="checkbox"/>	N	<input checked="" type="checkbox"/>	L1	<input type="checkbox"/>	L2	<input type="checkbox"/>	L3
	<input type="checkbox"/>	DC mains input power	<input type="checkbox"/>	Positive (+)		<input type="checkbox"/>	Negative (-)			
Voltage – Mains [V]	120 Vac									
Frequency – Mains [Hz]	50 Hz									
Test method applied	<input checked="" type="checkbox"/>	Artificial mains network								
	<input type="checkbox"/>	Voltage probe								
Test setup	<input type="checkbox"/>	Table top	<input checked="" type="checkbox"/>	Artificial hand applied						
	<input type="checkbox"/>	Floor standing	<input type="checkbox"/>	Other:						
	Refer to the Annex 3 for test setup photo(s).									
Operating mode(s) used	Mode 1									
Remark	---									

Measurement data	Port under test	AC mains power input
Operating mode / voltage / frequency used during the test		Mode 1/ 120 Vac/ 50 Hz

Line




No	Frequency (MHz)	Emission Level (dBuV)	Limit (dBuV)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	0.15	63.55	75.99	-12.44	53.88	9.67	QP
*2	0.15	57.26	68.98	-11.72	47.59	9.67	AV
3	0.224	55.52	73.40	-17.88	45.83	9.68	QP
4	0.224	48.58	65.28	-16.71	38.89	9.68	AV
5	0.428	51.59	69.00	-17.41	41.87	9.73	QP
6	0.428	40.74	59.00	-18.26	31.02	9.73	AV
7	0.575	51.58	69.00	-17.42	41.82	9.75	QP
8	0.575	38.44	59.00	-20.56	28.68	9.75	AV
9	0.999	50.75	69.00	-18.25	40.93	9.82	QP
10	0.999	40.02	59.00	-18.98	30.20	9.82	AV
11	1.394	49.62	69.00	-19.38	39.78	9.83	QP
12	1.394	40.09	59.00	-18.91	30.26	9.83	AV
13	1.54	48.54	69.00	-20.46	38.70	9.84	QP
14	1.54	39.84	59.00	-19.16	30.00	9.84	AV
15	2	46.36	69.00	-22.64	36.51	9.85	QP
16	2	37.85	59.00	-21.15	28.00	9.85	AV
17	3.46	41.89	69.00	-27.11	32.00	9.88	QP

Measurement data				Port under test		AC mains power input	
18	3.46	33.62	59.00	-25.38	23.73	9.88	AV
19	5.867	35.10	74.00	-38.90	25.13	9.96	QP
20	5.867	26.17	64.00	-37.83	16.21	9.96	AV
21	10.029	33.19	74.00	-40.81	23.08	10.11	QP
22	10.029	24.62	64.00	-39.38	14.51	10.11	AV
23	15.078	40.46	74.00	-33.54	30.26	10.20	QP
24	15.078	33.33	64.00	-30.67	23.13	10.20	AV
25	19.77	43.16	74.00	-30.84	32.89	10.28	QP
26	19.77	34.33	64.00	-29.67	24.05	10.28	AV
27	21.5	29.41	74.00	-44.59	19.12	10.29	QP
28	21.5	18.89	64.00	-45.11	8.60	10.29	AV
29	28.427	11.44	74.00	-62.56	1.11	10.33	QP
30	28.427	6.37	64.00	-57.63	-3.96	10.33	AV
Remark							

Measurement data	Port under test	AC mains power input
Operating mode / voltage / frequency used during the test		Mode 1/ 120 Vac/ 50 Hz

Neutral



No	Frequency (MHz)	Emission Level (dBuV)	Limit (dBuV)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	0.155	62.88	75.81	-12.93	53.21	9.67	QP
*2	0.155	56.71	68.73	-12.02	47.04	9.67	AV
3	0.248	55.70	72.56	-16.86	46.01	9.69	QP
4	0.248	47.09	64.09	-17.00	37.40	9.69	AV
5	0.344	54.14	69.19	-15.06	44.43	9.71	QP
6	0.344	43.58	59.28	-15.70	33.87	9.71	AV
7	0.422	53.57	69.00	-15.43	43.85	9.72	QP
8	0.422	41.35	59.00	-17.65	31.63	9.72	AV
9	0.545	52.85	69.00	-16.15	43.10	9.75	QP
10	0.545	38.75	59.00	-20.25	29.00	9.75	AV
11	1.019	50.75	69.00	-18.25	40.93	9.82	QP
12	1.019	39.79	59.00	-19.21	29.97	9.82	AV
13	1.111	49.46	69.00	-19.54	39.64	9.82	QP
14	1.111	40.07	59.00	-18.93	30.24	9.82	AV
15	1.859	46.57	69.00	-22.43	36.73	9.85	QP
16	1.859	38.57	59.00	-20.43	28.72	9.85	AV
17	3.265	42.73	69.00	-26.27	32.85	9.88	QP

Measurement data				Port under test		AC mains power input	
18	3.265	34.39	59.00	-24.61	24.51	9.88	AV
19	5.878	35.01	74.00	-38.99	25.04	9.97	QP
20	5.878	26.07	64.00	-37.93	16.10	9.97	AV
21	9.661	32.15	74.00	-41.85	22.02	10.12	QP
22	9.661	23.91	64.00	-40.09	13.79	10.12	AV
23	19.958	42.18	74.00	-31.82	31.75	10.43	QP
24	19.958	32.90	64.00	-31.10	22.47	10.43	AV
25	21.602	29.20	74.00	-44.80	18.74	10.45	QP
26	21.602	18.60	64.00	-45.40	8.14	10.45	AV
27	29.554	11.98	74.00	-62.02	1.39	10.59	QP
28	29.554	7.04	64.00	-56.96	-3.54	10.59	AV
Remark							

4.2 Conducted disturbance voltage– Load terminals	VERDICT: N/A
--	---------------------

Standard	EN 55014-1
Basic standard	EN 55016-2-1

Limits

Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾	Limit: AV [dB(μV) ¹⁾	IF BW	Detector(s)
0,15 - 0,50	80	70	9 KHz	QP, CAV
5,0 - 30	74	64	9 KHz	QP, CAV

¹⁾ At the transition frequency, the lower limit applies.

Performed measurements

Port(s) / Terminal(s) under test	
<input type="checkbox"/> (please write the name of the port under test)	<input type="checkbox"/> Other:
<input type="checkbox"/> Other:	<input type="checkbox"/> Other:
Voltage—Mains [V]	(Please write the voltage/voltages used for testing)
Frequency—Mains [Hz]	(Please write the frequency/frequencies used for testing)
Test method applied	<input type="checkbox"/> Voltage probe
	<input type="checkbox"/> ISN—Impedance Stabilisation Network
	<input type="checkbox"/> GDN according to EN / IEC 61000-4-6
	<input type="checkbox"/> Current probe
	<input type="checkbox"/> Artificial mains network
Test setup	<input type="checkbox"/> Table top <input type="checkbox"/> Artificial hand-applied
	<input type="checkbox"/> Floor-standing <input type="checkbox"/> Other:
	Refer to the Annex 3 for test setup photo(s).
Operating mode(s) used	Please write the operating mode(s) used during testing
Remark	---

4.3 Conducted disturbance voltage– Additional terminals	VERDICT: N/A
--	---------------------

Standard	EN 55014-1
Basic standard	EN 55016-2-1

Limits

Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾	Limit: AV [dB(μV) ¹⁾	IF BW	Detector(s)
0,15 - 0,50	80	70	9 KHz	QP, CAV
5,0 - 30	74	64	9 KHz	QP, CAV

¹⁾ At the transition frequency, the lower limit applies.

Performed measurements

Port(s) / Terminal(s) under test			
<input type="checkbox"/>	(please write the name of the port under test)		<input type="checkbox"/> Other:
<input type="checkbox"/>	Other:		<input type="checkbox"/> Other:
Voltage—Mains [V]		(Please write the voltage/voltages used for testing)	
Frequency—Mains [Hz]		(Please write the frequency/frequencies used for testing)	
Test method applied	<input type="checkbox"/>	GDN according to EN / IEC 61000-4-6	
	<input type="checkbox"/>	ISN—Impedance Stabilisation Network	
	<input type="checkbox"/>	Voltage probe	
	<input type="checkbox"/>	Current probe	
	<input type="checkbox"/>	Artificial mains network	
	<input type="checkbox"/>	Other:	
Test setup	<input type="checkbox"/>	Table top	<input type="checkbox"/> Artificial hand-applied
	<input type="checkbox"/>	Floor-standing	<input type="checkbox"/> Other:
	Refer to the Annex 3 for test setup photo(s).		
Operating mode(s) used	Please write the operating mode(s) used during testing		
Remark	---		

4.4 Disturbance power (30 MHz – 300 MHz)	VERDICT: PASS
---	----------------------

Standard	EN 55014-1
Basic standard	EN 55016-2-2


Limits – Tools

Frequency range [MHz]	Limit: QP [dB(pW)]	Limit: AV [dB(pW)]	IF BW	Detector(s)
30 - 300	45 – 55 ¹⁾	35 – 45 ¹⁾	120 KHz	QP, CAV
Margin				
200 - 300	0 – 10 ¹⁾	---	120 KHz	QP, CAV
¹⁾ The limit increases linearly with the frequency.				
<input type="checkbox"/>	Rated power below 700 W		Limits as above	
<input type="checkbox"/>	Rated power between 700 and 1000 W		Limits +4 dB	
<input checked="" type="checkbox"/>	Rated power above 1000 W		Limits +10 dB	

Performed measurements

Port(s) under test						
<input checked="" type="checkbox"/>	AC mains input power	<input type="checkbox"/>	Load	<input type="checkbox"/>	Control	
<input type="checkbox"/>	Other:	<input type="checkbox"/>	Other:	<input type="checkbox"/>	Other:	
Scan range (0,9 – 1,1 U _N)	<input type="checkbox"/>	198 – 264 V _{AC}	<input type="checkbox"/>	207 – 253 V _{AC}	<input checked="" type="checkbox"/>	230 V _{AC}
Voltage – Mains [V]	230 Vac					
Frequency – Mains [Hz]	50 Hz					
Test setup	<input checked="" type="checkbox"/>	Table top	<input type="checkbox"/>	Floor standing		
	<input type="checkbox"/>	Other:				
Refer to the Annex 3 for test setup photo(s).						
Conditions for exemption from measurements above 300 MHz	<input checked="" type="checkbox"/>	"Limits" reduced by "Margin" applied and passed				
	<input type="checkbox"/>	Maximum clock frequency < 30 MHz				
Operating mode(s) used	Mode 1					
Remark	---					

Measurement data	Port under test	AC mains power input
Operating mode / voltage / frequency used during the test		Mode 1/ 230 Vac/ 50 Hz




No	Frequency (MHz)	Emission Level (dBpW)	Limit (dBpW)	Margin (dB)	Reading Level (dBpW)	Correct Factor (dB)	Detector Type
1	31.38	29.06	55.05	-25.99	4.80	24.26	QP
*2	31.38	21.83	45.05	-23.22	-2.43	24.26	AV
3	46.47	30.78	55.61	-24.83	7.50	23.29	QP
4	46.47	19.93	45.61	-25.68	-3.35	23.29	AV
5	65.07	27.99	56.30	-28.31	4.99	23.00	QP
6	65.07	15.83	46.30	-30.46	-7.16	23.00	AV
7	88.17	28.27	57.15	-28.88	6.04	22.24	QP
8	88.17	15.01	47.15	-32.15	-7.23	22.24	AV
9	115.71	31.27	58.17	-26.91	8.84	22.43	QP
10	115.71	15.95	48.17	-32.23	-6.48	22.43	AV
11	151.56	25.46	59.50	-34.04	4.15	21.31	QP
12	151.56	14.23	49.50	-35.27	-7.08	21.31	AV
13	181.23	24.08	60.60	-36.52	3.73	20.35	QP
14	181.23	13.37	50.60	-37.23	-6.98	20.35	AV
15	221.348	24.15	62.09	-37.94	3.73	20.42	QP
16	221.348	12.78	52.09	-39.30	-7.64	20.42	AV
17	297.93	28.34	64.92	-36.58	7.81	20.53	QP
18	297.93	13.91	54.92	-41.01	-6.61	20.53	AV

Remark

Performed measurements

Port(s) under test						
<input checked="" type="checkbox"/>	AC mains input power	<input type="checkbox"/>	Load	<input type="checkbox"/>	Control	
<input type="checkbox"/>	Other:	<input type="checkbox"/>	Other:	<input type="checkbox"/>	Other:	
Scan range (0,9 – 1,1 U_N)	<input type="checkbox"/>	198 – 264 V _{AC}	<input type="checkbox"/>	207 – 253 V _{AC}	<input checked="" type="checkbox"/>	120 V _{AC}
Voltage – Mains [V]	120 Vac					
Frequency – Mains [Hz]	50 Hz					
Test setup	<input checked="" type="checkbox"/>	Table top	<input type="checkbox"/>	Floor standing		
	<input type="checkbox"/>	Other:				
	Refer to the Annex 3 for test setup photo(s).					
Conditions for exemption from measurements above 300 MHz	<input checked="" type="checkbox"/>	"Limits" reduced by "Margin" applied and passed				
	<input type="checkbox"/>	Maximum clock frequency < 30 MHz				
Operating mode(s) used	Mode 1					
Remark	---					

Measurement data	Port under test	AC mains power input
Operating mode / voltage / frequency used during the test		Mode 1/ 120 Vac/ 50 Hz



No	Frequency (MHz)	Emission Level (dBpW)	Limit (dBpW)	Margin (dB)	Reading Level (dBpW)	Correct Factor (dB)	Detector Type
1	31.47	31.08	55.05	-23.97	6.83	24.25	QP
2	31.47	23.66	45.05	-21.39	-0.59	24.25	AV
3	45.93	26.51	55.59	-29.08	3.23	23.28	QP
4	45.93	17.23	45.59	-28.36	-6.05	23.28	AV
*5	65.79	36.85	56.33	-19.47	13.99	22.86	QP
6	65.79	19.65	46.33	-26.67	-3.21	22.86	AV
7	80.55	26.44	56.87	-30.43	4.13	22.31	QP
8	80.55	14.50	46.87	-32.38	-7.82	22.31	AV
9	89.46	25.80	57.20	-31.40	3.57	22.23	QP
10	89.46	15.83	47.20	-31.38	-6.40	22.23	AV
11	129.96	30.48	58.70	-28.22	8.32	22.16	QP
12	129.96	16.81	48.70	-31.89	-5.35	22.16	AV
13	138.51	26.53	59.02	-32.49	4.64	21.89	QP
14	138.51	17.93	49.02	-31.09	-3.96	21.89	AV
15	148.14	24.22	59.38	-35.15	2.76	21.46	QP
16	148.14	14.08	49.38	-35.30	-7.39	21.46	AV
17	178.62	19.81	60.50	-40.69	-0.59	20.41	QP

18	178.62	12.57	50.50	-37.94	-7.84	20.41	AV
19	222.27	22.29	62.12	-39.83	1.85	20.45	QP
20	222.27	12.28	52.12	-39.84	-8.17	20.45	AV
21	296.73	19.00	64.88	-45.88	-1.52	20.51	QP
22	296.73	11.72	54.88	-43.16	-8.80	20.51	AV

Remark	
--------	--

4.5 Radiated electromagnetic disturbances (30 – 1000 MHz)	VERDICT: N/A
--	---------------------

Standard	EN 55014-1
Basic standard	EN 55016-2-3
Test method	Antenna method according to EN 55016-2-3 standard.

Limits

Frequency [MHz]	Limit: QP [dB(μV/m) ¹⁾			IF BW	Detector
	@3 m.	@5 m.	@10 m.		
30 - 230	40	36	30	120 KHz	QP
230 - 1000	47	43	37	120 KHz	QP

¹⁾ At the transition frequency, the lower limit applies.

Performed measurements

Port under test	Enclosure				
Voltage — Mains [V]	(Please write the voltage/voltages used for testing)				
Frequency — Mains [Hz]	(Please write the frequency/frequencies used for testing)				
Test method applied	<input checked="" type="checkbox"/>	OATS or SAC with measurement distance [m]: 3 m.			
	<input type="checkbox"/>	OATS or SAC with measurement distance [m]: 5 m.			
	<input type="checkbox"/>	OATS or SAC with measurement distance [m]: 10 m.			
Test setup	<input checked="" type="checkbox"/>	Equipment on a table of 80 cm height			
	<input type="checkbox"/>	Equipment on the floor (insulated from ground plane)			
	<input type="checkbox"/>	Other:			
Refer to the Annex 3 for test setup photo(s).					
Operating mode(s) used	Please write the operating mode(s) used during testing				
Remark	---				

4.6 Discontinuous disturbance (clicks) on AC power leads	VERDICT: N/A
---	---------------------

Standard	EN 55014-1		
Frequency [MHz]	Limit: QP [dB(μV)]	IF BW	Detector
0,15	66	9 KHz	Quasi-Peak (QP)
0,50	56	9 KHz	Quasi-Peak (QP)
1,40	56	9 KHz	Quasi-Peak (QP)
30,0	60	9 KHz	Quasi-Peak (QP)

Performed measurements

Scan range (0,9 – 1,1 U _N)	<input checked="" type="checkbox"/> 198 – 264 V _{AC}	<input type="checkbox"/> 207 – 253 V _{AC}	<input type="checkbox"/> – V _{AC}
Voltage – Mains [V]	264 Vac		
Frequency – Mains [Hz]	50 Hz		
Test method applied	<input checked="" type="checkbox"/> Artificial mains network		
	<input type="checkbox"/> Voltage probe		
Test setup	<input checked="" type="checkbox"/> Table top	<input type="checkbox"/> Floor standing	
	<input type="checkbox"/> Other:		
Operating mode(s) used	Mode 1		
Remark	---		

Reason for not performing the test	<input checked="" type="checkbox"/> The amplitudes of the observed disturbances were all below the limit for continuous disturbance, these are not considered to be clicks.
------------------------------------	---

Measurement results	<input checked="" type="checkbox"/> Neutral	<input checked="" type="checkbox"/> Line 1	<input type="checkbox"/> Line 2	<input type="checkbox"/> Line 3
---------------------	---	--	---------------------------------	---------------------------------

Frequency (MHz)	First Measurement: Determination of the limit L _{qp} – Quasi-peak							
	Limit L (dBμV)	Number of short clicks	Number of long clicks	Number of clicks – N ₁	Time of meas. (min.)	Click rate N	Increased limit (dB)	Increased Limit L _q
0,15	66	0	0	0	2			
0,5	56	0	0	0	2			
1,4	56	0	0	0	2			
30	60	0	0	0	2			

The calculated click rate N is not more than 5 times per minute and all the clicks are classified as short (t ≤ 10 ms). Thus, the EUT is deemed to comply with the limits without any further measurement at an increased limit.

Frequency (MHz)	Second measurement with Limit = L _q (Upper quartile method):			
	Limit L _q (dBμV)	Number of clicks – N ₂	Number of authorized clicks N ₂ ≤ N ₁ /4	Verdict
0,15				
0,5				
1,4				
30				

Supplementary information: ---

4.7 Harmonic current emissions	VERDICT: PASS
---------------------------------------	----------------------


Standard	EN 61000-3-2	
Exclusions (For these categories of equipment, limits are not specified in the EN 61000-3-2 standard)	<input type="checkbox"/>	Arc welding equipment intended for professional use.
	<input type="checkbox"/>	System(s) with nominal voltage(s) less than 220 V _{AC} (line-to-neutral).
	<input type="checkbox"/>	Equipment with rated power of ≤ 75 W (other than lighting equipment).
	<input type="checkbox"/>	Professional equipment with total rated power > 1 kW.
	<input type="checkbox"/>	Symmetrically controlled heating elements with a rated power ≥ 200 W.
	<input type="checkbox"/>	Independent dimmers for incandescent lamps with rated power ≤ 1 kW.

Classification			
<input type="checkbox"/>	Class A	All apparatus not classified as Class B, C or D	
<input checked="" type="checkbox"/>	Class B	Portable tools	
<input type="checkbox"/>	Class C	<input type="checkbox"/>	Lighting equipment with active input power > 25 W
		<input type="checkbox"/>	Lighting equipment with active input power ≤ 25 W (First requirement, Table 3 column 2)
		<input type="checkbox"/>	Lighting equipment with active input power ≤ 25 W (Second requirement)
<input type="checkbox"/>	Class D	Personal computers, television receivers	

Performed measurements

Port under test	AC mains power input					
Voltage – Mains [V]	230 Vac					
Frequency – Mains [Hz]	50 Hz					
Observation period	<input type="checkbox"/>	6.5 min.	<input checked="" type="checkbox"/>	2.5 min.	<input type="checkbox"/>	Other:
Version of measurement instrument standard used EN / IEC61000-4-7 (Cl. 7)	<input checked="" type="checkbox"/>	EN 61000-4-7:2002 + AM1:2009 (IEC 61000-4-7:2002+AM1:2008)				
	<input type="checkbox"/>	EN 61000-4-7:1991				
Control principle used in the EUT	<input checked="" type="checkbox"/>	Comply with the requirements of the Clause 6.1 (EN / IEC 61000-3-2).				
	<input type="checkbox"/>	Not comply with the requirements of the Clause 6.1 (EN / IEC 61000-3-2).				
Operating mode(s) used	Mode 1					
Remark						

Measurement data	Port under test	AC mains power input
Operating mode / voltage / frequency used during the test		Mode 1/ 230 Vac/ 50 Hz



Harmonic Emission - IEC 61000-3-2 , EN 61000-3-2 , (EN60555-2)

2020/4/7 下午 01:25:27

Urms = 229.9 V P = 875.5 W THC = 2.739 A
 Irms = 5.151 A pf = 0.739

Range: 25 A
 V-nom: 230 V
 TestTime: 5 min (100%)

Test completed, Result: PASSED

Temperature (°C) :20 ; Relative Humidity (%RH) :64

HAR-1000 EMC-Partner

Measurement data				Port under test		AC mains power input				
Urms =	229.9V	Freq =	49.987	Range:	25 A					
Irms =	5.151A	l _{pk} =	11.44A	cf =	2.220					
P =	875.5W	S =	1184VA	pf =	0.739					
THDi =	62.3 %	THDu =	0.20 %	Class B						
Test - Time :		5min		(100 %)						
Test completed, Result: PASSED										
Order	Freq. [Hz]	l _{avg} [A]	Irms [A]	Irms% [%]	Irms%L [%]	l _{max} [A]	l _{max} % [%]	l _{max} %L [%]	Limit [A]	Status
1	50	4.4773	4.3961	85.338		4.7302	91.825			0.00
2	100	0.0000	0.0183	0.3555	1.1303	0.0214	0.4147	1.3187	1.6200	0.00
3	150	2.5867	2.5528	49.556	73.994	2.6596	51.629	77.090	3.4500	0.00
4	200	0.0000	0.0153	0.2962	2.3657	0.0183	0.3555	2.8388	0.6450	0.00
5	250	0.9296	0.9232	17.921	53.986	0.9506	18.454	55.592	1.7100	0.00
6	300	0.0000	0.0137	0.2666	3.0518	0.0137	0.2666	3.0518	0.4500	0.00
7	350	0.2972	0.3036	5.8945	26.290	0.3098	6.0130	26.818	1.1550	0.00
8	400	0.0000	0.0107	0.2073	3.0960	0.0122	0.2370	3.5383	0.3450	0.00
9	450	0.0765	0.0778	1.5107	12.970	0.0824	1.5995	13.733	0.6000	0.00
10	500	0.0000	0.0168	0.3258	6.0814	0.0183	0.3555	6.6343	0.2760	0.00
11	550	0.0000	0.0244	0.4739	4.9321	0.0290	0.5628	5.8569	0.4950	0.00
12	600	0.0000	0.0229	0.4443	9.9514	0.0244	0.4739	10.615	0.2300	0.00
13	650	0.0617	0.0732	1.4218	23.251	0.0748	1.4514	23.736	0.3150	0.00
14	700	0.0187	0.0336	0.6517	17.028	0.0351	0.6813	17.802	0.1971	0.00
15	750	0.0603	0.0595	1.1552	26.449	0.0626	1.2145	27.805	0.2250	0.00
16	800	0.0004	0.0275	0.5332	15.922	0.0305	0.5924	17.691	0.1725	0.00
17	850	0.0602	0.0671	1.3033	33.818	0.0702	1.3626	35.355	0.1985	0.00
18	900	0.0000	0.0107	0.2073	6.9660	0.0153	0.2962	9.9514	0.1533	0.00
19	950	0.0597	0.0626	1.2145	35.220	0.0641	1.2441	36.079	0.1776	0.00
20	1000	0.0000	0.0076	0.1481	5.5285	0.0092	0.1777	6.6343	0.1380	0.00
21	1050	0.0489	0.0504	0.9775	31.331	0.0519	1.0071	32.281	0.1607	0.00
22	1100	0.0000	0.0092	0.1777	7.2977	0.0107	0.2073	8.5140	0.1255	0.00
23	1150	0.0467	0.0519	1.0071	35.355	0.0519	1.0071	35.355	0.1467	0.00
24	1200	0.0000	0.0092	0.1777	7.9611	0.0107	0.2073	9.2880	0.1150	0.00
25	1250	0.0380	0.0366	0.7109	27.127	0.0397	0.7701	29.387	0.1350	0.00
26	1300	0.0000	0.0061	0.1185	5.7497	0.0076	0.1481	7.1871	0.1062	0.00
27	1350	0.0219	0.0351	0.6813	28.076	0.0366	0.7109	29.297	0.1250	0.00
28	1400	0.0000	0.0076	0.1481	7.7400	0.0107	0.2073	10.836	0.0986	0.00
29	1450	0.0036	0.0305	0.5924	26.223	0.0305	0.5924	26.223	0.1164	0.00
30	1500	0.0000	0.0153	0.2962	16.586	0.0198	0.3851	21.561	0.0920	0.00
31	1550	0.0000	0.0244	0.4739	22.425	0.0259	0.5036	23.826	0.1089	0.00
32	1600	0.0000	0.0198	0.3851	22.999	0.0229	0.4443	26.537	0.0862	0.00
33	1650	0.0000	0.0244	0.4739	23.872	0.0259	0.5036	25.363	0.1023	0.00
34	1700	0.0000	0.0122	0.2370	15.038	0.0137	0.2666	16.917	0.0812	0.00
35	1750	0.0000	0.0198	0.3851	20.571	0.0214	0.4147	22.154	0.0964	0.00
36	1800	0.0000	0.0046	0.0889	5.9708	0.0046	0.0889	5.9708	0.0767	0.00
37	1850	0.0000	0.0198	0.3851	21.747	0.0214	0.4147	23.419	0.0912	0.00
38	1900	0.0000	0.0031	0.0592	4.2017	0.0046	0.0889	6.3025	0.0726	0.00
39	1950	0.0000	0.0183	0.3555	21.159	0.0198	0.3851	22.922	0.0865	0.00
40	2000	0.0000	0.0031	0.0592	4.4228	0.0031	0.0592	4.4228	0.0690	0.00

Measurement data		Port under test	AC mains power input
Order		Limits in Ampere	
		100%	150%
2		1.6205	2.4307
3		3.4500	5.1750
4		0.6454	0.9682
5		1.7105	2.5658
6		0.4501	0.6752
7		1.1551	1.7326
8		0.3448	0.5173
9		0.5997	0.8995
10		0.2762	0.4143
11		0.4944	0.7416
12		0.2304	0.3456
13		0.3143	0.4715
14		0.1968	0.2953
15		0.2243	0.3365
16		0.1724	0.2586
17		0.1984	0.2975
18		0.1526	0.2289
19		0.1770	0.2655
20		0.1373	0.2060
21 *		0.1602	0.2403
22		0.1251	0.1877
23 *		0.1465	0.2197
24		0.1144	0.1717
25 *		0.1343	0.2014
26		0.1068	0.1602
27 *		0.1251	0.1877
28		0.0992	0.1488
29 *		0.1160	0.1740
30		0.0916	0.1373
31 *		0.1083	0.1625
32		0.0870	0.1305
33 *		0.1022	0.1534
34		0.0809	0.1213
35 *		0.0961	0.1442
36		0.0763	0.1144
37 *		0.0916	0.1373
38		0.0732	0.1099
39 *		0.0870	0.1305
40		0.0687	0.1030
Remark			

4.8 Voltage changes, voltage fluctuations and flicker	VERDICT: PASS
--	----------------------

Standard	EN 61000-3-3
----------	--------------

Limits

P _{ST} (Short term flicker)	<input type="checkbox"/>	≤ 1	<input checked="" type="checkbox"/>	Not Applicable
P _{LT} (Long term flicker)	<input type="checkbox"/>	≤ 0,65	<input checked="" type="checkbox"/>	Not Applicable
d _c (Relative Voltage change)	<input checked="" type="checkbox"/>	≤ 3,3%	<input type="checkbox"/>	Not Applicable
d _{MAX} (Max. voltage change)	<input type="checkbox"/>	≤ 4%	<input type="checkbox"/>	6%
	<input checked="" type="checkbox"/>	7%	<input type="checkbox"/>	Not Applicable
<u>Supplemental information:</u>				

Performed measurements

Reason for not performing the measurement(s)	<input type="checkbox"/>	Tests are not necessary because the EUT is unlikely to produce significant voltage fluctuations or flicker (clause 6.1).				
Port under test	AC Mains power input					
Voltage – Mains [V]	230 Vac					
Frequency – Mains [Hz]	50 Hz					
Test method	<input checked="" type="checkbox"/>	Flickermeter according EN / IEC 61000-4-15:2011				
	<input type="checkbox"/>	Simulation (Clause 4.2.3 of EN / IEC 61000-3-3)				
	<input type="checkbox"/>	Analytical method (Clause 4.2.4 of EN / IEC 61000-3-3)				
	<input type="checkbox"/>	Use of P _{st} = 1 curve (Clause 4.2.5 of EN / IEC 61000-3-3)				
Observation period	<input type="checkbox"/>	10 min.	<input type="checkbox"/>	120 min.	<input type="checkbox"/>	Other:
	<input checked="" type="checkbox"/>	24 times switching according to Annex B				
Operating mode(s) used	Mode 1					
Remark	---					

See next page.

Measurement data	Port under test	AC mains power input										
Operating mode used during the test	Mode1/ 230 Vac/ 50 Hz											
<table border="1"> <tbody> <tr> <td data-bbox="193 477 1002 517">Relative voltage change characteristic dt</td> <td data-bbox="1002 477 1337 517">0,0</td> </tr> <tr> <td data-bbox="193 517 1002 557">Maximum voltage change d_{MAX}</td> <td data-bbox="1002 517 1337 557">2,49%</td> </tr> <tr> <td data-bbox="193 557 1002 598">Relative Voltage change d_c</td> <td data-bbox="1002 557 1337 598">1,50%</td> </tr> <tr> <td data-bbox="193 598 1002 638">Short term flicker P_{ST}</td> <td data-bbox="1002 598 1337 638">Not applicable</td> </tr> <tr> <td data-bbox="193 638 1002 678">Long term flicker P_{LT}</td> <td data-bbox="1002 638 1337 678">Not applicable</td> </tr> </tbody> </table>			Relative voltage change characteristic dt	0,0	Maximum voltage change d _{MAX}	2,49%	Relative Voltage change d _c	1,50%	Short term flicker P _{ST}	Not applicable	Long term flicker P _{LT}	Not applicable
Relative voltage change characteristic dt	0,0											
Maximum voltage change d _{MAX}	2,49%											
Relative Voltage change d _c	1,50%											
Short term flicker P _{ST}	Not applicable											
Long term flicker P _{LT}	Not applicable											
Remark												

5 IMMUNITY TEST RESULTS

5.1 Performance (Compliance) criteria

[According to EN 55014-2 (CISPR 14-2)]

Performance criteria A : The apparatus shall continue to operate as intended during the test. No degradation of performance or loss of function is allowed below a performance level (or permissible loss of performance) specified by the manufacturer when the apparatus is used as intended. If the minimum performance level or the permissible performance loss is not specified by the manufacturer then either of these may be derived from the product description and documentation and from what the user may reasonably expect from the apparatus if used as intended.

Performance criteria B : The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level (or permissible loss of performance) specified by the manufacturer when the apparatus is used as intended. During the test, degradation of performance is allowed however no change of actual operating state or stored data is allowed. If the minimum performance level or the permissible performance loss is not specified by the manufacturer then either of these may be derived from the product description and documentation and from what the user may reasonable expect from the apparatus if used as intended.

Performance criteria C : Temporary loss of function is allowed provided the function is self- recoverable or can be restored by the operation of the controls or by any operation specified in the instruction for use.

5.1.1 Performance criteria related to immunity tests

Immunity test	Performance criteria
Electrostatic discharge	B
Radio-frequency electromagnetic fields	A
Fast transients	B
Surge transient	B
Injected currents (radio-frequency common mode)	A
Voltage dips and short interruptions	C

5.1.2 Manufacturer defined performance criteria

Not provided.

5.2 Monitored – Checked Functions / Parameters

During the immunity tests the following functions of the EUT has/have been monitored/checked.

<input checked="" type="checkbox"/>	Motor speed	<input type="checkbox"/>	Display data
<input type="checkbox"/>	Switching	<input type="checkbox"/>	Data storage
<input type="checkbox"/>	Standby mode	<input type="checkbox"/>	Sensor functions
<input type="checkbox"/>	Temperature	<input type="checkbox"/>	Audible signals
<input type="checkbox"/>	Power consumption	<input type="checkbox"/>	Others : LED's
<input type="checkbox"/>	AC mains input current	<input type="checkbox"/>	Others :
<input type="checkbox"/>	Timing	<input type="checkbox"/>	Others :
<input type="checkbox"/>	Illumination	<input type="checkbox"/>	Others :
<u>Supplementary information :</u>			

Immunity test	Monitored - Checked function(s)/parameter(s) during / after the test	Method
Electrostatic discharge	PASS	Visual
Radio-frequency electromagnetic fields	N/A	---
Fast transients	PASS	Visual
Surge transient	PASS	Visual
Injected currents (radio-frequency common mode)	PASS	Visual
Voltage dips and short interruptions	PASS	Visual
<u>Supplementary information :</u>		

5.3 Electrostatic discharge immunity	VERDICT: PASS
---	----------------------

Electrostatic discharges (ESD) are the result of persons or objects that accumulate static electricity due to for instance walking on synthetic carpets. The ESD can influence the operation of equipment or damage its electronics, either by a direct discharge or indirectly by coupling or radiation. Both effects are simulated during the tests.

Requirements

Standard	EN 55014-2							
Basic standard	EN 61000-4-2							
Port under test	Enclosure							
Air discharges ¹⁾	<input type="checkbox"/>	±2 kV	<input type="checkbox"/>	±4 kV	<input checked="" type="checkbox"/>	±8 kV	<input type="checkbox"/>	kV
Contact discharges ¹⁾	<input type="checkbox"/>	±2 kV	<input checked="" type="checkbox"/>	±4 kV	<input type="checkbox"/>	±8 kV	<input type="checkbox"/>	kV
Number of discharges	≥ 10 per polarity with ≥ 1 sec interval.							
¹⁾ Tests with lower voltages are not required.								

Performed tests

Set-up	<input checked="" type="checkbox"/>	Table-top	<input type="checkbox"/>	Floor standing
Ambient temperature [°C]	23 °C		Relative Humidity air [%]	46.1%
Voltage – Mains [V]	230 Vac/ 120 Vac			
Frequency – Mains [Hz]	50 Hz			
Operating mode(s) used	Mode 1			

Test Point	Test Voltage [kV] & Polarity	Coupling type	# of applied discharges / polarity	Discharge interval [s]
<input checked="" type="checkbox"/> Points on conductive surface as indicated in the picture below.	±4	Contact	10	1
<input checked="" type="checkbox"/> Points on non-conductive surface as indicated in the picture below.	±8	Air	10	1
<input checked="" type="checkbox"/> HCP top side.	±4	Contact	10	1
<input checked="" type="checkbox"/> HCP bottom side.	±4	Contact	10	1
<input checked="" type="checkbox"/> VCP right side.	±4	Contact	10	1
<input checked="" type="checkbox"/> VCP left side.	±4	Contact	10	1
<input checked="" type="checkbox"/> VCP front side.	±4	Contact	10	1
<input checked="" type="checkbox"/> VCP rear side.	±4	Contact	10	1
Observation(s)	During the test no loss of performance was observed. After the test the EUT functioned as intended. No unacceptable loss of performance or data was observed.			
Supplementary information:				

5.4	Radio-frequency electromagnetic fields immunity	VERDICT: N/A
------------	--	---------------------

During the test it is verified if the equipment under test (EUT) has sufficient immunity against radiated electromagnetic fields. Industrial electromagnetic sources, walkie-talkies, radio transmitters, television transmitters and telecommunication equipment including cellular telephones and other emitting devices can generate these fields.

Requirements

Standard	EN 55014-2			
Basic standard	EN 61000-4-3			
Port under test	Enclosure			
Frequency range	Test level	Modulation	Dwell time	Step size
80 – 1000 MHz	3 V/m	80% AM (1kHz)	≥ 0,5 s	≤ 1%
<u>Supplementary information:</u>				

Performed tests

Test method	<input checked="" type="checkbox"/>	EN 61000-4-3	<input type="checkbox"/>	EN 61000-4-20		
Test set-up	<input checked="" type="checkbox"/>	Equipment on the table (0,8 m height)				
	<input type="checkbox"/>	Equipment standing on floor (0,05—0,15 m height)				
Voltage—Mains [V]	230 Vac					
Frequency—Mains [Hz]	50 Hz					
Operating mode(s) used	Mode 1					
Frequency range (applied)	Antenna Polarization	Test level (applied)	Modulation (applied)	Dwell time (applied)	Remark	
80—1000 MHz (step size 1%)	H	3 V/m	80% AM (1kHz)	3 s		
	V	3 V/m	80% AM (1kHz)	3 s		
Exposed side of the EUT	<input checked="" type="checkbox"/>	Front (0°)	<input checked="" type="checkbox"/>	Right (90°)	<input type="checkbox"/>	Top
	<input checked="" type="checkbox"/>	Rear (180°)	<input checked="" type="checkbox"/>	Left (270°)	<input type="checkbox"/>	Bottom
Observation(s)	During the test no loss of performance was observed. After the test the EUT functioned as intended. No unacceptable loss of performance was observed.					
<u>Supplementary information:</u>						

5.5 Electrical Fast Transients immunity	VERDICT: PASS
--	----------------------

The EFT immunity test simulates disturbances by bursts of very short transients caused for example by switching off loads such as an AC motor or bouncing relay contacts. The transients are likely to disturb electronics but less likely to cause damage.

Requirements

Standard	EN 55014-2			
Basic standard	EN 61000-4-4			
Pulse characteristics	5/50 ns			
Port	Test level	Repetition frequency	Duration	
<input checked="" type="checkbox"/> AC input-output power ¹⁾	± 1000 V	5 KHz	2 min. / polarity	
<input type="checkbox"/> DC input-output power ²⁾	± 500 V	5 KHz	2 min. / polarity	
<input type="checkbox"/> Signal and Control lines ³⁾	± 500 V	5 KHz	2 min. / polarity	
¹⁾ For extra low voltage a.c ports, this testing is only applicable to ports interfacing with cables whose total length may exceed 3 m according to the manufacturer's functional specification. ²⁾ Not applicable to battery operated appliances that cannot be connected to the mains while in use. ³⁾ Applicable only to ports interfacing with cables whose total length may exceed 3 m according to the manufacturer's functional specification.				

Performed tests

Voltage – Mains [V]	230 Vac/ 120 Vac			
Frequency – Mains [Hz]	50 Hz			
Operating mode(s) used	Mode 1			
Test Set-up	<input checked="" type="checkbox"/>	Equipment standing on floor at (0,1 ± 0,01) m above ground plane		
	<input type="checkbox"/>	Equipment on the table (0,1 ± 0,01) m above ground plane		
	<input type="checkbox"/>	Artificial hand applied.		
Coupling	<input checked="" type="checkbox"/>	Common mode	<input type="checkbox"/>	Other:

Port(s) under test	Test Voltage & Polarity	Repetition Frequency	Test duration / polarity	Injection method		
AC / DC mains power input	1 kV	5 KHz	2 min	<input checked="" type="checkbox"/>	CDN	<input type="checkbox"/> Clamp
AC / DC power output		5 KHz		<input type="checkbox"/>	CDN	<input type="checkbox"/> Clamp
Ethernet / LAN		5 KHz		<input type="checkbox"/>	CDN	<input type="checkbox"/> Clamp
Observation(s)	During the test no loss of performance was observed. After the test the EUT functioned as intended. No unacceptable loss of performance was observed.					

5.6	Surge transient immunity	VERDICT: PASS
------------	---------------------------------	----------------------

The surge transient immunity test simulates the surges that are caused by over-voltages due to indirect (induced) lightning transients. The pulse is a slow transient with high-energy contents and due to its long duration may cause damage to an unprotected EUT.

Requirements

Standard	EN 55014-2		
Basic standard	EN 61000-4-5		
Pulse characteristics	1,2/50µs Voltage; 8/20µs Current		
Repetition rate	≥ 60 secs. (for each test level and phase angle)		
Number of pulses	5 pulses (at each polarity and phase angle)		
Port	Test level & Polarity & Coupling		Phase angle [°]
	Line to Line	Line to Earth	
AC input power ¹⁾	+ 1 kV	N/A	90
AC input power ¹⁾	- 1 kV	N/A	270
¹⁾ Tests with lower voltages are not required.			

Performed tests

Voltage – Mains [V]	230 Vac/ 120 Vac
Frequency – Mains [Hz]	50 Hz
Operating mode(s) used	Mode 1
Repetition rate	60 secs. (for each test level and phase angle)
Number of pulses	5 pulses (at each polarity and phase angle)

Port(s) under test	Coupling	Test level & Polarity	Phase angle [°]	Remark
<input checked="" type="checkbox"/> AC mains input power	Line to Neutral	+1 kV	90	
<input checked="" type="checkbox"/> AC mains input power	Line to Neutral	-1 kV	270	
<input type="checkbox"/> AC mains input power	Line to Earth	+2 kV	90	1
<input type="checkbox"/> AC mains input power	Line to Earth	-2 kV	270	1
<input type="checkbox"/> AC mains input power	Neutral to Earth	+2 kV	90	1
<input type="checkbox"/> AC mains input power	Neutral to Earth	-2 kV	270	1
Observation(s)	During the test no loss of performance was observed. After the test the EUT functioned as intended. No unacceptable loss of performance or data was observed.			
<u>Supplementary information:</u>				
1. The EUT does not include an earth port.				

5.7	Injected currents (RF common mode) immunity	VERDICT: PASS
------------	--	----------------------

During this test the immunity of the equipment for induced or conducted electromagnetic fields is checked. Fields generated by radio and other transmitters cause RF voltages in long cables like the mains network. This test reproduces these induced disturbing voltages by injecting them to the EUT via the cabling.

Requirements

Standard		EN 55014-2		
Basic standard		EN 61000-4-6		
Frequency range		Modulation	Step size	Dwell time
<input type="checkbox"/>	0,15 – 80 MHz	80% AM (1kHz)	≤ 1%	≥ 0,5 s
<input checked="" type="checkbox"/>	0,15 – 230 MHz	80% AM (1kHz)	≤ 1%	≥ 0,5 s
Port			Test level, U _o	
<input checked="" type="checkbox"/>	AC input-output power ¹⁾		3 V	
<input type="checkbox"/>	DC input-output power ^{2) 3)}		1 V	
<input type="checkbox"/>	Signal and Control lines ⁴⁾		1 V	
¹⁾ For extra low voltage a.c ports, this testing is only applicable to ports interfacing with cables whose total length may exceed 3 m according to the manufacturer's functional specification. ²⁾ Not applicable to battery operated appliances that cannot be connected to the mains while in use. ³⁾ Applicable to battery operated appliances that can be connected to the mains while in use, or to appliances for which the length of d.c. cables may exceed 3 m according to the manufacturer's functional specification. ⁴⁾ Applicable only to ports interfacing with cables whose total length may exceed 3 m according to the manufacturer's functional specification.				

Performed tests

Frequency range (applied)		Modulation (applied)		Step size (applied)
<input type="checkbox"/>	0,15 – 80 MHz	<input checked="" type="checkbox"/>	0,15 – 230 MHz	80% AM (1kHz) 1%
Voltage – Mains [V]		230 Vac/ 120 Vac		Frequency – Mains [Hz] 50 Hz
Operating mode(s) used		Mode 1		
Test set-up		<input type="checkbox"/> Equipment standing on floor at (0,1 ± 0,01) m above ground plane. <input type="checkbox"/> Equipment on the table (0,1 ± 0,01) m above ground plane. <input checked="" type="checkbox"/> Artificial hand applied.		

Port(s) under test	Test Level (applied)	Injection method	Dwell time (applied)	Remark
AC mains power input	3 V	CDN-M2	3 s	

Observation(s)	During the test no loss of performance was observed. After the test the EUT functioned as intended. No unacceptable loss of performance or data was observed.
Supplementary information:	

5.8	Power supply interruptions and dips immunity	VERDICT: N/A
------------	---	---------------------

The purpose of the test is to verify the immunity of the equipment against voltage dips and voltage interruptions. It helps to ensure that the equipment functions properly (as expected and safely) with power supply fluctuations. Voltage dips and interruptions are caused by faults in the LV, MV, HV networks (short-circuit or ground faults).

Requirements

Standard	EN 55014-2			
Basic standard	EN 61000-4-11			
# of dips & interruptions	3 dips / interruptions for each test level and phase angle			
Interval between events	≥ 10 seconds			
Port	Test level ¹⁾	Period (Cycles)		Performance Criteria
		50 Hz	60 Hz	
AC input power port	$U_{NOM} - 100\%$	0,5	0,5	C; Refer to the chapter 5.1 for details.
AC input power port	$U_{NOM} - 60\%$	10	12	C; Refer to the chapter 5.1 for details.
AC input power port	$U_{NOM} - 30\%$	25	30	C; Refer to the chapter 5.1 for details.
¹⁾ Changes to the voltage level shall occur at a zero crossing point in the a.c. voltage waveform. NOTE: Where the equipment has a rated voltage range the following shall apply: <ul style="list-style-type: none"> - If the voltage range does not exceed 20% of the lower voltage specified for the rated voltage range. A single voltage within that range may be selected for testing. - In all other cases, the test procedure shall be applied for both the lowest and highest voltages declared in the voltage range. 				

Performed tests

U_{NOM} [V _{AC}]	Terminal	Voltage dip [% U_{NOM}]	Duration [cycles]		Repetition rate [s]	Number of dips per test	Phase angle [°]
			50 Hz	60 Hz			
230	L-N	0	0,5	/	10	3	0, 180
230	L-N	40	10	/	10	3	0, 180
230	L-N	70	25	/	10	3	0, 180
120	L-N	0	0,5	/	10	3	0, 180
120	L-N	40	10	/	10	3	0, 180
120	L-N	70	25	/	10	3	0, 180
Operating mode(s) used		Mode 1					
Observation(s)		During the test no loss of performance was observed. After the test the EUT functioned as intended. No unacceptable loss of performance was observed.					
<u>Supplementary information:</u>							

6 IDENTIFICATION OF THE EQUIPMENT UNDER TEST

EUT PHOTOS

7 MEASUREMENT UNCERTAINTIES

The table(s) below show(s) measurement uncertainties of the EMC test set-ups. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Conducted Emissions

The measurement uncertainty is evaluated as ± 2.26 dB.

Disturbance Power Emission

The measurement uncertainty is evaluated as ± 3.34 dB.

Harmonic Current Emission

The measurement uncertainty is evaluated as 0.1%.

Voltage Fluctuation and Flicker

The measurement uncertainty is evaluated as $\pm 4\%$.

8 USED EQUIPMENT

Conducted Emission / SR2-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
Test Receiver	R&S	ESR3	102608	2019/07/03	2020/07/02
Artificial Mains Network	R&S	ENV4200	848411/010	2020/01/08	2021/01/07
LISN	R&S	ENV216	100092	2019/07/09	2020/07/08
Coaxial Cable(9m)	Belden	8129	SR2-H	2019/08/15	2020/08/14
DEKRA-EMI system	DEKRA	Version 1.0	SR2-H	N/A	N/A

Disturbance Power Emission / SR2-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
Test Receiver	R&S	ESC17	100879	2019/07/03	2020/07/02
Absorbing Clamp	Luthi	MDS 21B	P1602169770	2020/01/16	2021/01/15
Coaxial Cable(5m)	Schwarzbeck	RG-223U	SR2-H-PT	2019/08/15	2020/08/14
DEKRA-EMI system	DEKRA	Version 1.0	SR2-H	N/A	N/A

Power Harmonics / SR3-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
EMC Emission Tester	EMC-Partner	HAR-1000-1P	109	2019/12/17	2020/12/16

Voltage Fluctuation and Flicker / SR3-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
EMC Emission Tester	EMC-Partner	HAR-1000-1P	109	2019/12/17	2020/12/16

Electrostatic Discharge / SR8-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
Electrostatic Simulator Discharge	NoiseKen	ESS-2002	ESS04Z3759	2019/06/11	2020/06/09
Horizontal Coupling Plane (HCP)	QuieTek	HCP AL50	N/A	N/A	N/A
Vertical Coupling Plane (VCP)	QuieTek	HCP AL50	N/A	N/A	N/A

Electrical fast transient/ Brust / SR3-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
EMC Immunity Tester	Teseq	NSG 3060	1424	2019/07/09	2020/07/08
Clamper	Haefely	093 506.1	083 593-23	2020/01/02	2021/01/01

Surge / SR3-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
EMC Immunity Tester	Teseq	NSG 3060	1424	2019/07/09	2020/07/08
CDN	Teseq	CDN 118	47916	2020/01/02	2021/01/01
CDN	Teseq	CDN 118	47917	2020/01/02	2021/01/01

Conducted susceptibility / SR7-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
Compact Immunity Test System	Teseq	NSG 4070b-80	41145	2019/12/17	2020/12/16
CDN	Schafner	CDN M016	16337	2019/10/07	2020/10/06
CDN	Schafner	CDN T400	16905	2019/10/07	2020/10/06
CDN	Teseq	CDN T800	52751	2019/10/24	2020/10/24
CDN	Teseq	CDN T8-10	38994	2019/10/07	2020/10/06
Immunity Injection Clamp	Schafner	KENZ801	15928	2019/10/14	2020/10/13
6Db PAD	JFW	50FHAO-06-100	N/A	N/A	N/A

Voltage dips and interruptions / SR7-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
EMC Immunity Tester	Teseq	NSG 3060	1424	2019/07/09	2020/07/08

9 TEST PHOTOS

Conducted disturbance voltage at mains terminals




Disturbance power




H & F




Surge & EFT & DIPS



CS



ESD



-----END-----