

Page 1 of 3

EU_GD_IEC 60 745-1F

Clause

Requirement + Test

Result - Remark

Verdict

ATTACHMENT TO TEST REPORT IEC 60745-1 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES

Hand-held motor-operated electric tools - Safety - Part 1: General requirements

 Differences according to.....
 EN 60745-1 : 2009

 Attachment Form No.....
 EU_GD_IEC60745_1F

Attachment Originator TÜV SÜD Product Service GmbH

Master Attachment: Date (2009-08)

	CENELEC COMMON MODIFICATIONS (EN)		
6	ENVIRONMENTAL REQUIREMENTS		Р
6.1	Noise (Test according to § 6.1.1 – § 6.1.2.8)		Р
	Noise measurements:		Р
6.1.2.9	Declaration and verification of noise emission values		Ρ
	LpA [dB(A)]: KpA [dB(A)]	95,5 3 dB(A)	Р
	LpCpeak (dB): KpCpeak (dB)		N/A
	LWA [dB(A)]: KWA [dB(A)]	106,5	Р
6.2	Vibration (Test according to § 6.2.1 – § 6.2.6)		Р
	Vibration measurements		Р
6.2.7.1	Reported vibration value		Р
	Work mode - vibration emission value a (m/s ²):	2,8 m/s ²	Р
	Uncertainty K (m/s ²):	1,5 m/s²	Р
6.2.7.2	Declaration of the vibration emission value (instruction manual)		Р
	Work mode - vibration emission value a (m/s ²):	2,8 m/s ²	Р
	Uncertainty K (m/s ²):	1,5 m/s²	Р
8	MARKINGS AND INSTRUCTIONS		Р
8.1	Business name and address of the manufacturer and, where applicable, his authorised representative:	LEE YEONG INDUSTRIAL CO., LTD. No.2, Kejia Rd., Douliu City, Yunlin County 64057, Taiwan	—
	Designation of the tool:	Wall chaser	—



Page 2 of 3

EU_GD_IEC 60 745-1F

21	CONSTRUCTION		Р
	 of the need to identify safety measures to protect the operator that are based on an estimation of exposure in the actual conditions of use (taking account of all parts of the operating cycle such as the times when the tool is switched off and when it is running idle in addition to the trigger time). 		P
	 that the vibration emission during actual use of the power tool can differ from the declared total value depending on the ways in which the tool is used; and 		P
	5) A warning:		Р
	- that the declared vibration total value may also be used in a preliminary assessment of exposure.		P
	- that the declared vibration total value has been measured in accordance with a standard test method and may be used for comparing one tool with another.		P
	4) The following information:		Р
	Vibration emission > 2.5 m/s ² value given in the instruction		Р
	Vibration emission < 2.5 m/s ² , stated in the instruction		N/A
	3) The vibration emission according to 6.2.		Р
	 Recommendation for the operator to wear hearing protection. 		Р
	1) The noise emission according to 6.1.2.		Р
8.12.2 (Za)	Emissions (EN 60745-1:2009)		
	<i>Additional:</i> They include the designation of the tool and series or type as required by 8.1, including description of machine such as "drill", "planer" etc.		Р
	<i>Replacement:</i> They include the business name and address of the manufacturer and, where applicable, his authorised representative. Any address are sufficient to ensure contact.		Р
8.12	Additional: The translations must be bear the words "Translation of the original instructions", and they must be accompanied by a copy of the "Original instructions".		P
	Year of manufacture	2020 and later	—
	Designation of series or type:	CG125; CG5; CW125; SL-1255	—
Clause	Requirement + Test	Result - Remark	Verdict



Page 3 of 3

EU_GD_IEC 60 745-1F			
Clause	Requirement + Test	Result - Remark	Verdict
21.Z1	Additional: In normal use a dust hazard to health is expected		Р
	following point must be fulfilled:a) Integral dust collection devices, or		N/A
	b) Devices, which allow the connection of external dust collection equipment, or		Р
	if not reasonably protected practicable, no dust is thrown in the direction of the operator.		N/A

ANNEX K BATTERY TOOLS AND BATTERY PACKS N/A

ANNEX L	BATTERY TOOLS AND BATTERY PACKS PROVIDED WITH MAINS CONNECTION OR NON-ISOLATED SOURCES	N/A
---------	---	-----

|--|

ZC	ANNEX ZC, NATIONAL DEVIATIONS (EN)	N/A
EndEnd		