



# G7 CONCRETE GRINDER

May. 2024

Internal & Confidential

**AGP** | G7 Concrete Grinder

#### **AGP TAIWAN**

Lee Yeong Industrial Co., Ltd.

No.2, Kejia Rd., Douliu City, 64057, Taiwan

Tel: 886-5-5518689 Fax: 886-5-5518635

#### AGP EUROPE BV

Evenbroekveld 16D, 9420 Erpe-Mere, Belgium Tel: +32 53 21 62 22 Fax: +32 53 83 88 20



# Introduction Target group & Applications

## **G7 Introduction & Applications**

The G7 is optimized to use 180mm cup wheels for faster progress on larger areas. The G7 is purpose-built and designed for ideal concrete grinding performance while maintaining strict dust control. The variable constant speed function gives

the tool excellent versatility. Since the offset height of cup wheels varies, we offer a pair of arbor spacers to compensate, as needed, for wheels with less offset.

By using different types of diamond cup wheels, a vast array of different tasks can be done; from rough grinding and leveling, to stripping coatings, to surface preparation for applying coatings.

## **Target Groups**

- Renovation Contractors
- New Construction Contractors
- Tilers and Floor Installers
- Stonemasons
- Specialists





## **Sales Arguments**





1 Variable speed for different applications



Effective dust control skirt with spring suspension



2 Anti-vibration mountings for maximum operator comfor



Tool-free sliding cover for edge grinding



Replaceable brush bristles for smooth action and efficient dust containment



6 Optional Floor Grinding Trolley

# **Technical Specifications**



Model	G7	
Power Input	220-240 V : 2200 W	
	110-120 V : 1700 W	
Voltage	110-120 V~ 50-60 Hz or	
	220-240 V~ 50-60 Hz	
No Load Speeds	3200 - 6500 min <sup>-1</sup>	
Wheel Diameter	180 mm (7")	
Arbor	22.23 mm (7/8")	
Spindle	M14	
Dimensions (LxWxH)	246 x 280 x 325 mm	
Weight	6.0 kg (13.2 lb)	

## **Offer Content**

## **Standard Accessories**

- **1** G7 Concrete Grinder
- Blow Molded Case
- 3 Lock Nut Wrench
- 4 Face Spanner Wrench
- M6 L-Hex Key
- 6 Arbor Spacer (2), used to compensate for cup wheels with less offset.

### **Recommended Item**

- Floor Grinding Trolley
- 8 DS25L Vacuum Cleaner







Blow Molded Case



3 Lock Nut Wrench



**6** M6 L-Hex Key

00

**Face Spanner Wrench** 

6 Arbor Spacers



Floor Grinding Trolley

## **Offer Content**

## **Standard Accessories**

- **1** G7 Concrete Grinder
- Blow Molded Case
- 3 Lock Nut Wrench
- Face Spanner Wrench
- M6 L-Hex Key
- 6 Arbor Spacer (2), used to compensate for cup wheels with less offset.

### **Recommended Item**

- Floor Grinding Trolley
- 8 DS25L Vacuum Cleaner





- 3 Lock Nut Wrench
- ich 👍 Face Spanner Wrench





- M6 L-Hex Key
- 6 Arbor Spacers







2 Blow Molded Case







8 DS25L Vacuum Cleaner

## **Comparison Table**

**Brand** 

180 mm Vertical-Type Concrete Grinder







Model	G7	EBS 180 H
Power Input	2200 W	2500 W
Rated Load Speed	3 200 - 6 500 min <sup>-1</sup>	8 500 min <sup>-1</sup>
Wheel Ø	180 mm	180 mm
Variable speed	Yes	No
Soft Start & Overload Protection	Yes	Yes
Constant Speed	Yes	No
Dust Skirt with Brush	Yes	Yes
Spring Suspension Dust Skirt	Yes	No
Half-moon Door for Edge Grinding	Yes	Yes
Anti-Vibration Handle Mounts	Yes	Yes
Floor Grinding Trolley	optional	optional (model EBS 180 F)
Weight	6.0 kg	8.4 kg
Conclusion	The <b>AGP</b> has many features which are missing on the Competitor's machine, like spring suspension, variable speed, and constant speed electronics. In addition, the optional <b>AGP</b> floor grinding trolley is more functional and user-friendly, because of its side handle design, the <b>AGP</b> floor grinding trolley allows much better control and leverage for the operator.	

# Tool Dimensions (mm)

